

Performance

•Qualcomm Snapdragon 5G CPU with up to 2.0 GHz •Android 11 OS and 4GB RAM + 64GB ROM storage

·10.1 inch IPS full HD screen with 10-point capacitive touch

Communication

Qualcomm mobile platform integrates 5G baseband
 Support 5G Sub–6GHz carrier aggregation main frequency band,
 SA and NSA network deployment
 4G/3G/2G, dual–band Wi–Fi 5 and BT 5.1

Product Six Views

Function

Professional 2D scan engine and multi-function NFC
GPS, BDS, GLONASS, Galileo, NavIC (IRNSS), multi-satellite navigation system

·Equipped with multiple accessories, like docking charger, hand-strap, vehicle mount, shoulder-strap, back-strape

Reliability

- ·IP65 Waterproof and Dustproof
- ·Impact resistance: Drop from a height of 1.22 meters
- ·In accordance with MIL-STD-810G



Specification Parameter

| Basic parameters | | Performance parameter | |
|---------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------|--------------------------------------------------------------------------------------|
| Dimension | 275.7 x 187.5 x 24.5mm | CPU | Qualcomm(OCTA Core), 2.0GHz |
| Weight | device unit 1000g | OS | Android 11 |
| Device Color | black | RAM | 4GB |
| LCD | 10.1 inch IPS 16:10, 1200x1920, 400nits | ROM | 64GB |
| Touch Panel | 10 point G+G capacitive touch screen | Battery | |
| Camera | Front 5.0MP Rear 13.0MP | Capacity | 3.7V/8000mAh |
| Ι/Ο | USB 3.0 Type-A x 1, USB Type-C x 1, SIM Card x 1, TF Card x 1, HDMI 1.4a x 1, 12pins Pogo Pin x 1, Φ3.5mm standard earphone jack x 1, Φ3.5mm DC jack x 1 | Туре | Built-in Li-polymer battery |
| | | Endurance | 7hrs (50% volume sounds, 200 lumens brightness, 1080P HD video display by default) |
| | | Data Collection | |
| Power | AC100V ~ 240V, 50Hz/60Hz, Output DC 5V/3A | NFC | Built-in, ISO/IEC 14443A |
| Communication | | | |
| WIFI | WiFi 802.11 a/b/g/n/ac (2.4G+5G) | 2D | Optional, Honeywell N3680 |
| Bluetooth | BT5.1 | Reliability | |
| | 5G NR: N1/41/78/79 | Operate Temperature | –10 °C ~ 50 °C |
| 2G/3G/4G/5G (Optional) | TDD–LTE: B34/38/39/40/41 FDD–LTE: B1/3/5/7/8 | Store Temperature | –20 °C ~ 60 °C |
| | WCDMA: B1/5/8 | Humidity | 95% Non-Condensing |
| GNSS | Built-in GPS L1&L5/Beidou/Glonass/Galileo/NavIC/IRNSS | Rugged Feature | IP65 certified, MIL-STD-810G certified |
| | | Drop Height | 1.22m |

Accessories





Docking Charger

Hand-strap



Vehicle Mount

Application Range

Various modules and accessories can be selected to meet customers' application in various industries.

