

# NISE 2400-J1900



Intel® Celeron® Processor J1900 Quad Core Fanless System



## Main Features

- ♦ Onboard Intel® Celeron® Processor J1900 Quad Core, 2.0GHz
- ♦ Dual independent display from DVI-I and HDMI
- ♦ 2 x Intel® I210IT GbE LAN ports; support WoL, teaming and PXE
- ♦ 4 x USB 2.0 & 1 x USB 3.0
- ♦ 2 x RS232 & 2 x RS232/RS422/RS485 with auto flow control
- ♦ 2 x mini PCIe socket for optional mSATA/Wi-Fi/4G LTE/3.5G/Fieldbus modules
- ♦ Support -5 to 55 degree Celus extended operating temperature
- ♦ Support 9-30V DC input

## Product Overview

Powered by Intel® Celeron® Processor J1900 Quad Core, 2.0GHz. Driven by the latest Quad Core Intel® Celeron® Processor, NIE2400-J1900 can provide excellent computing power and is more power-efficient than the platforms based on the previous generation Intel® Celeron® product family.

NISE2400-J900 supports up to 8G DDR3L memory and have several options on storage devices like CFast, HDD, SSD or mSATA . The NISE2400-J900 comes with 1 x HDMI, 1 x DVI-I, 2 x GbE LAN ports, 2x COM port with RS232/422/485 and 5x USB ports including one USB 3.0. NISE2400-J900 supports 9~30V DC input, and can be operated in an extended operating temperature range from -5 to 55 degrees Celsius. This Fanless system supports two mini PCIe modules, which can be an excellent platform for IOT applications (with optional GbE LAN, Wi-Fi, 3.5G/4G LTE module) and factory automation applications with optional fieldbus module. Its expansion versatility makes NISE2400-J900 a perfect platform for factory automation and M2M intelligent computing applications.

## Specifications

### CPU Support

- ♦ Onboard Intel® Celeron® Processor J1900 Quad Core, 2.0GHz
- ♦ Support Intel® Atom™ E3800 processor family from single core E3815, dual core E3825/E3826/E3827 and quad core E3845 with difference SKUs

### Main Memory

- ♦ 2 x DDR3L SO-DIMM socket, support DDR3L 1066/1333 8GB RAM max., un-buffered and non-ECC

### Display Option

- ♦ Dual independent display
  - HDMI and DVI-I
  - HDMI and VGA (via DVI-I connector)

### Front I/O Interface

- ♦ ATX power on/off switch
- ♦ 1 x Power status, 1 x HDD access, 1 x battery low, 4 x programming LEDs, 4 x Tx/Rx LEDs, 2 x LAN LEDs
- ♦ 2 x DB9 RS232 for COM3 & COM4
- ♦ 1 x External CFast socket
- ♦ 1 x SIM card holder
- ♦ 1 x USB 3.0 (900mA per each)

- ♦ 1 x Mic-in & 1 x Line-out
- ♦ 2 x Antenna holes for optional Wi-Fi/3.5G antenna

### I/O Interface - Rear

- ♦ 4 x USB 2.0
- ♦ 1 x DVI-I display output
- ♦ 1 x HDMI display output
- ♦ 1 x Remote power on/off switch
- ♦ 2 x Intel® I210IT GbE LAN ports; support WoL, teaming and PXE
- ♦ 2 x DB9 for COM1 & COM2, both support RS232/422/485 with auto flow control
  - Jumper-free setting on RS232/422/485
- ♦ 1 x 3-pin DC input, support +9 to 30VDC input

### I/O Interface - Internal

- ♦ 4 x GPIO and 4 GPO (5V, TTL type)


### Storage Device

- ♦ 1 x CFast card socket (SATA 2.0)
- ♦ 1 x 2.5" HDD space (SATA 2.0)
- ♦ 1 x mSATA from mini PCIe socket if SATA HDD is not installed

### Expansion Slot

- ♦ 2 x mini PCIe socket for optional Wi-Fi/4G LTE/3.5G

## Dimension Drawing



### Power Requirement

- ♦ Power input: +9Vdc to +30Vdc
- ♦ 1 x Optional 24V, 60W power adapter

### Dimensions

- ♦ 191mm (W) x 200mm (D) x 60mm (H) without wall-mount bracket

### Construction

- ♦ Aluminum and metal chassis with fanless design

### Environment

- ♦ Operating temperature:  
Ambient with air flow: -5°C to 55°C  
(according to IEC60068-2-1, IEC60068-2-2, IEC60068-2-14)
- ♦ Storage temperature: -30°C to 85°C
- ♦ Relative humidity: 10% to 95% (non-condensing)
- ♦ Shock protection:  
HDD: 20G, half sine, 11ms, IEC60068-2-27  
CFast: 50G, half sine, 11ms, IEC60068-2-27
- ♦ Vibration protection w/ HDD condition:  
Random: 0.5Grms @ 5~500Hz, IEC60068-2-64  
Sinusoidal: 0.5Grms @ 5~500Hz, IEC60068-2-6
- ♦ Vibration protection w/ CFast & SSD condition:  
Random: 2Grms @ 5~500Hz, IEC60068-2-64  
Sinusoidal: 2Grms @ 5~500Hz, IEC60068-2-6

### Certifications

- ♦ CE
- ♦ FCC Class A

### OS Support Lists

- ♦ Windows 8, 32-bit/64-bit
- ♦ Windows Embedded Standard 8, 32-bit/64-bit
- ♦ Windows 7, 32-bit/64-bit
- ♦ Windows Embedded Standard 7, 32-bit/64-bit
- ♦ Windows 10 IoT Enterprise, 64-bit
- ♦ Linux Kernel version 3.8.0

## Ordering Information

### Barebone

- ♦ **NISE 2400-J1900 (P/N:10J00240002X0)**  
Onboard Intel® Celeron® Processor J1900 Quad Core, 2.0GHz
- ♦ **24V 60W AC/DC power adapter w/o power cord  
(P/N: 7400060024X00)**



IP SYSTEMES

8 rue du Colonel Chambonnet – BP67

69672 BRON Cedex

Tel. : 04 72 14 18 00

Fax : 04 72 14 18 01

[www.ip-systemes.com](http://www.ip-systemes.com) – [info@ip-systemes.fr](mailto:info@ip-systemes.fr)