



Main Features

- 4:3 8" SVGA fanless panel computer
- Intel® Atom™ E3826, Dual Core, low power consumption CPU
- Flush panel by 5-wire touch screen
- Dual GbE/2nd display-VGA/2x RS232/422/485/Line-out
- 3 x USB 2.0/1 x USB 3.0/1 x mini-PCIe socket/1 x CFast
- Remote power switch
- DDR3L 2GB/2.5" HDD bracket
- IP65 compliant front panel
- Support Fieldbus module
- Mounting support: panel/wall/stand/VESA 75mm x 75mm
- Wide range power input 12~30VDC

Product Overview

Incorporated a 8" 4:3 touch screen LCD panel with resolutions up to 800 x 600 (SVGA) and 400 nits brightness, the APPC 0840T are fanless Panel PC based on the Atom™ E3826 processor. The industrial motherboard is reengineering to have RAM and mini-PCIe aligned in the same side of the board with its Intel® Atom™ E3826 CPU. This dedicated motherboard benefits users both in future capability expansion and ease for maintenance. The Panel PC comes with flush panel design and can have IP65 front for industrial applications. The touch screen provides the durable, reliable, and scratchable benefits for easy maintenance in wide applications.

The ultra slim APPC0840T makes it become industrial slimmest model for space-critical applications, such as, access control, small automation machineries, forklift and truck etc. This APPC 0840T supports fieldbus module, WWAN/WLAN expansion and others via dual Gigabit Ethernet connectors, one mini-PCIe slot and one SIM card holder. With support for wide power input of 12~30VDC, this APPC 0840T can gain a strong foothold in industrial field and machine devices. In addition, this APPC 0840T can hook 2nd display via a VGA port for dual independent display. 0840T has two RS232/422/485 ports, three USB 2.0 port, one USB 3.0 port and fieldbus port.

Specifications

Panel

- LCD size: 8", 4:3
- Resolution: SVGA 800 x 600
- Luminance: 400cd/m2
- Contrast ratio: 500
- LCD color: 262K
- Viewing angle: 50(U), 70(D), 70(L), 70(R)
- Backlight: LED

Touch screen

- 5-wire resistive (Flush panel type)
- Touch light transmission: 82%
- Touch interface: USB

System


- CPU: on-board Intel® Atom™ dual core processor E3826, 1.46GHz, 1M L2 cache
- BIOS: AMI BIOS
- System memory: 1x 204-pin DDR3L SO-DIMM socket, 2GB DDR3L (default), support up to 8GB DDR3L-1066/1333, non-ECC and un-buffered
- Storage device:

- 1 x external locked CFast socket
- 1 x hard drive bay: optional 1 x 2.5" SATA HDD or 1 x SATA DOM
- Watchdog timer: Watchdog timeout can be programmable by software from 1 second to 255 seconds and from 1 minute to 255 minutes (tolerance 15% under room temperature 25°C)
- H/W status monitor: monitoring system temperature, and voltage
- Expansion: 1 x mini-PCIe socket1 (support optional Wi-Fi, 3.5G module or fieldbus card)

Rear I/O

- Ethernet: 2 x RJ45
- 2nd display VGA port: 1 x DB15
- Audio port: 1 x Line-out
- USB: 3 x USB 2.0; 1 x USB 3.0
- Power switch
- Remote power switch
- Reset button
- COM #1: RS232/422/485
- COM #2: RS232/422/485
- Fieldbus: (protocol interface optional)

Dimension Drawing



Model	Protocol	Connector
FBI90E-PNM	PROFINET Master	Dual RJ-45
FBI90E-EP	EtherNet/IP Master	
FBI90E-ECM	EtherCAT Master	DB9
FBI90E-PBM	PROFIBUS Master	
FBI90E-DNM	DeviceNet Master	
		5-pins Phoenix contact terminal

Certifications

- ♦ CE approval
- ♦ FCC Class A

OS Support Lists

- ♦ Windows 8 32-bit/64-bit
- ♦ Windows 7 32-bit/64-bit
- ♦ WinCE 7.0

Audio

- ♦ HD codec: realtek ALC886-GR
- ♦ Audio interface: Line-out audio jack

Ethernet

- ♦ LAN chip: dual Intel® I210-AT Gigabit LAN
- ♦ Ethernet interface: 10/100/1000 Base-Tx Ethernet compatible

Mechanical & Environment

- ♦ Color: Pantone black
- ♦ IP protection: IP65 front
- ♦ Mounting: panel/wall/stand/VESA 75mm x 75mm
- ♦ System with panel mounting kit w/o panel mounting hole
- ♦ Power
 - Power input: 12~30VDC
 - Power adapter: optional AC to DC power adapter (+12V, 60W)
- ♦ Vibration
 - IEC 68 2-64 (w/ HDD)
 - 1Grms @ sine, 5~500Hz, 1hr/axis (HDD operating)
 - 2Grms @ sine, 5~500Hz, 1hr/axis (CFast operating)
 - 2.2Grms @ random condition, 5~500Hz, 0.5hr/axis (non-operating)
- ♦ Shock
 - IEC 68 2-27
 - HDD: 20G@wall mount, half sine, 11ms
- ♦ Temperature
 - Operating temperature: -5°C to 50°C
 - Storage temperature: -20°C to 75°C
- ♦ Operating humidity: 10%~90% relative humidity, non-condensing limits to be at 90% RH at max 50°C
- ♦ Dimension: 217.4x176.4x68.9mm
- ♦ Weight: 2.3 kg

Ordering Information

Barebone

- ♦ **APPC 0840T (P/N: 10IA0840T00X0)**
8" SVGA LED backlight touch panel PC with Intel® Atom™ E3826 1.46 GHz, touch screen, 2GB DDR3L with 2x RS232/422/485

Options

- ♦ **12V, 60W AC/DC power adapter w/o power cord (P/N: 7400060049X00)**
- ♦ **PROFINET, EtherNet/IP, EtherCAT, SERCOSIII master interface module: FBI 90E-REM (P/N: 10J50090E08X0)**
- ♦ **PROFINET master interface module: FBI 90E-PNM (P/N: 10J50090E21X0)**
- ♦ **PROFIBUS master interface module: FBI 90E-PBM (P/N: 10J50090E09X0)**
- ♦ **DeviceNet master interface module: FBI 90E-DNM (P/N: 10J50090E10X0)**
- ♦ **EtherCAT master interface module: FBI 90E-ECM (P/N: 10J50090E19X0)**