

# S50

4.5" Rugged PDA T9 Keyboard Mobile Handheld

## Overview

S50 intelligent terminal is ideal for highly mobile outdoor and field workers in markets like logistics, construction, mine, military, field sales and the public sector. It meets MIL-STD-810G and IP65 standards for durability and protection against dirt dust, water, motion, vibration, temperature and other factors that would quickly damage an industrial-grade handheld device. It can withstand up to a 1.8m drop and 2 ton shock pressure test. It also comes with a suite of integrated features, including an UHF RFID, 1D/2D barcode scanner, NFC. Also it goes with a long-life 5000mAh/10000mAh battery sunlight-readable, and operating under extreme low temperature.

## Features

- ARM Cortex A73 Octa-Core 2 GHz
- Operating System Android 10/11...
- Screen size 4.5-inch IPS, resolution 540x960 QHD
- Optional: 1D, 2D barcode reader, NFC, RFID
- Supports 4G, Wi-Fi, Bluetooth and GNSS
- High-capacity battery 5000mAh
- MIL-STD-810G & IP65 certified



## I/O Interfaces



## Specifications

DISPLAY		
Size	4.5-inch IPS/AFFS QHD	
Touch type	Capacitive/Frosted tempered film supports glove touch / spray / active capacitive pen	
Resolution	540 x 960	
Luminance	500 nits	
SYSTEM		
CPU	MediaTek MT6771 ARM Cortex-A73 Octa-Core 2.0 GHz	
Memory	4 GB	
Storage	32 GB	
External Memory	Micro SD Card (T-Flash Card), max 1TB	
Graphics	ARM Mali-G72 MP3	
Operating System	Android 10/11	
Camera	Main : 13.0MP (AF) with Flash Led	
Sensor	Gravity, Magnetic Field, Motion, Gyroscope, Light, Acceleration	
I/O PORTS		
USB	1x USB Type C OTG	
SIM Card	1.8/3.3V SIM Card	
TF Card	Micro SD Card (T-Flash card), max 1TB	
Charging interface	1x Type-C & 2-Pin Pogo Pin	
Headphone	3.5mm (CTIA)	
COMMUNICATION		
Wi-Fi	Dual-Band Wi-Fi (2.4GHz/5.0GHz), single stream 802.11 a/b/g/n/ac	
Bluetooth	Bluetooth V5.0 Low Energy (LE)	
Cellular	Phone Call : GSM/WCDMA/VoLTE 2G : GSM/EDGE/GPRS/WAP 2G BAND : GSM (B2/3/5/8) 3G : WCDMA 3.75G (HSPDA+42.2Mbps, HSUPA+11.5Mbps) 3G BAND : WCDMA (B1/2/5/8) 4G : FDD: 150Mbps down, 50Mbps UP TDD: 150 Mbps, 50Mbps UP 4G BAND : TD-LTE (B38/39/40/41); FDD LTE (B1, B2, B3, B4, B5, B7, B8, B12, B17, B20, B28)	
GNSS	GPS, GLONASS, BeiDou, AGPS, SBAS (EPO 2.5m)	
OPTIONAL MODULES		
Extension 1	UHF Module	(M500 ASTM) + Antenna (M500 EN) + Antenna
	LF RFID Module	125K LF ID Card (8H-10D) 125K LF ID Card (10D) 125K LF HID Card Module 134.2K LF Animal Tag Module

## 4.5" Rugged PDA T9 Keyboard Mobile Handheld

	HF RFID Module	13.56M HF module (single protocol) 13.56M HF module (multi protocol)
	1D/2D Barcode Module	
	RS-232 Module	Optional RS-232 serial port, using M8 5-Pin aviation plug to 9-Pin adapter
	NFC Module	
	Other customer supply modules	Need to meet the interface conditions: Powered by 3.3V-1.5A/5V-1.5A, UART interface, interface level 3.3V/5V, GPIO 1 /Electrical level 3.3V/5V
Extension 2	Battery	Optional 10000mAh – Replaceable battery
	NFC Module	
<b>ENVIRONMENT</b>		
Charger	5.0V 2A 10W	
Operating temperature	-20°C to 55°C	
Storage temperature	-40°C to 80°C	
Relative humidity	5% to 95%, non-condensing	
Operating Altitude	Max: 4,500m (15,000 feet)	
Shake-proof	1-19Hz /1.0mm; 19-200Hz/1.0g	
Dropproof / IK	MIL-STD-810G/Method516.6/Procedure IV & Touch Panel IK05	
Waterproof	Class 5 (IEC 60529)	
Dustproof	Class 6 (IEC 60529)	
Reliability	MTBF >5000h; MTTR <0.5h	
IP Rating	IP65 (IEC 60529)	
Language	French, English, Spanish, Portuguese (Brazil), Portuguese (Portugal), Italian, German, Dutch,, Polish, Romanian, Turkish, Russian, Arabic, Indonesian, Malay, Thai, Vietnamese, Hindi, Hebrew, Simplified, Chinese, Chinese Traditional,...	
<b>BATTERY</b>		
Battery type	5000mAh – Replaceable Battery	
<b>MECHANICAL</b>		
Dimensions (L x W x H mm)	197 x 92 x 26.5 mm	
Weight (kg)	420g	
Color	Black&Yellow, Black&Green, Black&Gray (PC+ABS+TPU)	
<b>CERTIFICATION</b>		
Certification	CE, 3C, ROHS, FCC	

# .S50

4.5" Rugged PDA T9 Keyboard Mobile Handheld

## Dimensions



## Ordering Information

Ref.	Description
S50	4.5", 540x960, 500 nits, MT6771, 4+32GB, Gray, Neutral