

.T70

7-Inch Full Rugged Ultra-bright HD PDA

Overview

T70 rugged PDA, tough appearance, is with 7" industrial-grade, 1000cd/m² full-view display, toughened glass TP, and also aero-grade titanium alloy material frame. It meets MIL-STD-810G/Method 516.6/Procedure IV and military standard. Ant it can be withstand up to a 1.5m drop and 2 ton shock pressure test. While, it also comes with a suite of integrated features, which is high-integration, high-performance, high-reliability, high-flexibility. Also it goes with a long-life 10000mAh Battery, sunlight-readable, and operating under extreme low temperature.

Features

- ARM Cortex A73 Octa-Core 2 GHz
- Operating System Android 9/10/11...
- Screen size 7-inch IPS, resolution 720x1280 HD
- Optional: NFC, RFID modules
- Supports 4G, Wi-Fi, Bluetooth and GNSS
- High-capacity battery 10000mAh
- MIL-STD-810G & IP67 certified



Android



High-capacity



IP67



RFID

I/O Interfaces



Specifications

DISPLAY	
Size	7-inch IPS/AFFS FHD
Touch type	Capacitive/Frosted tempered film supports glove touch / spray / active capacitive pen
Resolution	720x1280
Luminance	1000 nits Sunlight-Readable
SYSTEM	
CPU	MediaTek MT6771 ARM Cortex-A73 Octa-Core 2.0 GHz
Memory	8 GB
Storage	128 GB
External Memory	Micro SD Card (T-Flash Card), max 1TB
Graphics	ARM Mali-G72 MP3
Operating System	Android 9/10/11... (Continuous Updates)
Camera	Main : 13.0MP (AF) with Flash Led Sub camera : 5.0MP
Sensor	Gravity, Magnetic Field, Motion, Gyroscope, Light, Acceleration
I/O PORTS	
USB	1x USB Type C
SIM Card	1.8 / 3.3V SIM Card
TF Card	Micro SD Card (T-Flash Card), max 1TB
Charging interface	1x Type-C
Headphone	3.5mm (CTIA)
COMMUNICATION	
Wi-Fi	Dual-Band Wi-Fi (2.4GHz/5.0GHz), single stream 802.11 a/b/g/n/ac
Bluetooth	Bluetooth V5.0 Low Energy (LE)
Cellular	Phone Call : GSM/WCDMA/VoLTE 2G : GSM/EDGE/GPRS/WAP 2G BAND : GSM (B2/3/5/8) 3G : WCDMA 3.75G (HSPDA+42.2Mbps, HSUPA+11.5Mbps) 3G BAND : WCDMA (B1/2/5/8) 4G : FDD: 150Mbps down, 50Mbps UP TDD: 150 Mbps, 50Mbps UP 4G BAND : TD-LTE (B38/39/40/41); FDD LTE (B1, B2, B3, B4, B5, B7, B8, B12, B17, B20, B28)
GNSS	GPS, GLONASS, BeiDou, AGPS, SBAS (EPO 2.5m)
OPTIONAL MODULES	
Extension 1	NFC Module
Extension 2	HD 1612 (Beidou) + Ceramic Antenna HD 1612 5Glonass) + Ceramic Antenna
Extension 3	UHF Module (M500 ASTM) + Antenna (M500 EN) + Antenna

	<i>LF RFID Module</i>	125K LF ID Card (8H-10D) 125K LF ID (10D) 125K LF HID Card Module 134.2K LF Animal Tag Module
	<i>HF RFID Module</i>	13.56M HF module (single protocol) 13.56M HF module (multi-protocol)
	<i>Short-distance data communication module</i>	LoRa Zigbee
	<i>Serial Port Module</i>	UART RS-232
	<i>Other customer supply modules</i>	Need to meet the interface conditions: Powered by 3.3V-1.5A / 5V-1.5A, UART interface, interface level 3.3V/5V, GPIO 1/electrical level 3.3V/5V.

ENVIRONMENT

Charger	5.0V 2A 10W
Operating temperature	-20°C to 55°C
Storage temperature	-40°C to 80°C
Relative humidity	5% to 95%, non-condensing
Operating Altitude	Max: 4,500m (15,000 feet)
Shake-proof	1-19Hz /1.0mm; 19-200Hz/1.0g
Dropproof / IK	MIL-STD-810G/Method516.6/Procedure IV & Touch Panel IK05
Waterproof	Class 7 (IEC 60529)
Dustproof	Class 6 (IEC 60529)
Reliability	MTBF >5000h; MTTR <0.5h
IP Rating	IP67
Language	English, Spanish, Portuguese (Brazil), Portuguese (Portugal), Italian, German, Dutch, French, Polish, Romanian, Turkish, Russian, Arabic, Indonesian, Malay, Thai, Vietnamese, Hindi, Hebrew, Simplified, Chinese, Chinese Traditional,...

BATTERY

Battery type	10000mAh
--------------	----------

MECHANICAL

Dimensions (L x W x H mm)	200 x 132 x 21 mm
Weight (kg)	640g
Color	Black&Yellow, Black&Green, Black&Gray (PC+ABS+TPU)

CERTIFICATION

Certification	CE, 3C, ROHS, FCC
---------------	-------------------

.T70

7-Inch Full Rugged Ultra-bright HD PDA

Dimensions



Ordering Information

Ref.	Description
T70	7", 720x1280, 1000 nits, MT6771, 8+128GB, Gray, Neutral